



500 Series

and Model 680SS Hot-Water Pressure Washer

#1 in North America for
High-Pressure Cleaning Equipment

Oil- or LP-Fired

Hose reel (optional) makes hose mobility and storage easy and convenient. Also keeps work areas neat and safe while protecting hoses from damage

Built-in wand holder provides convenient storage

Stainless steel coil skin (555SS, 560SS & 680SS) provides extra durability to withstand the elements

2 to 2.3 HP, 115V, 1PH electric motor is drip proof and comes with thermal overload protection and manual reset

Upright, oil-fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Pressure relief valve protects the machine and user from thermal expansion

Convenient hose-reel bracket accepts swivel or stationary reels for ease in hose maneuverability and storage

50-ft. length of high-pressure hose for easy maneuverability around a large working area

Float tank helps maintain constant pressure and helps prevent sediment from entering the machine's components

Rust-proof, non-contaminating polyethylene fuel tank includes fuel gauge in cap



Simple, easy-to-use control panel includes adjustable temperature control plus heavy-duty heater and pump motor switches

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

37-ft. power cord with safety **Ground Fault Circuit Interrupter (GFCI breaker)**



Hotsy direct-drive, positive-displacement pumps carries seven-year warranty

A pressure switch is standard on all 500 Series models

Semi-pneumatic tires eliminate the risk of flats

Model 560SS:
2.1 GPM @ 1500 PSI (Shown with optional Hose Reel)

Adjustable, spray-angle nozzle with 0° to 80° spray patterns adjusts easily under high pressure



Model 558-Propane
2.2 GPM @ 1300 PSI
(Shown with optional Portagear and Propane Tank)



Model 555SS:
2.2 GPM @ 1300 PSI (Shown with optional Hose Reel)



Model 680SS:
3 GPM @ 1000 PSI

FEATURES

- Oil- or LP- Fired
- 2.1 to 3.0 GPM / 1000 to 1500 PSI
- Convenient 115 volt
- Direct Drive Pumps

Four industrial-grade models in compact, affordable packages!



Heater coil carries a 5-year warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

500 SERIES Hot Water Pressure Washers

■ Oil- or LP-Fired

■ 2.1 to 3.0 GPM / 1000 to 1500 PSI

■ 115V

■ Direct Drive

■ ETL-Certified

Four affordable models, designed for tough, industrial cleaning.

SPECIFICATIONS

DIRECT DRIVE

MODEL	GPM	PSI	HP	VOLTS/PH	AMP	FUEL	BTU/HR	PUMP	PORTABILITY	DIMENSIONS	HOSE	SHIP WT
555SS	2.2	1300	2	115/1	20	Oil	214,300	Hotsy Duplex	Std	33"Lx27"Wx41.5"H	50'	370
558	2.2	1300	2	115/1	18	LP	227,000	Hotsy Duplex	Optional	31.5"Lx26"Wx41"H	50'	320
560SS	2.1	1500	2.3	115/1	20	Oil	214,300	Hotsy Triplex	Std	33"Lx26"Wx44"H	50'	385
680SS	3.0	1000	2	115/1	20	Oil	289,900	Hotsy Triplex	Std	33"Lx27"Wx45.5"H	50'	385

SS = Stainless Steel



Clean better with Hotsy detergents

Hotsy pressure washers and parts washers clean best when matched with

specially formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Looking to save time and money? See a Hotsy foamer in action!



Spend some time with a Hotsy Expert

Hotsy has more than 160 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's distributors have been supporting Hotsy systems for more than 20 years.



Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.

hotsy Nothing Cleans Like a Hotsy!

Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 8.914-202.0 Effective 8/12 Specifications & product descriptions subject to change without notice. ©2012 Hotsy
 A member of KÄRCHER North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.


OPTIONS

- Float Tank (555SS)
- 8" LP Gas-Fired Draft Diverter (558)
- 8" Oil-Fired Draft Dampener (555SS/560SS/680SS)
- Portage Kit (558)
- Propane Tank (558)
- 360° Pivot Hose Reel - Available in 100' and 200'

Hotsy Accessories customize your application for top performance



High-pressure turbo nozzles for faster cleaning



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



Heavy-duty high-pressure hoses in lengths up to 150-ft.

Telescoping wands extend to 24' to reach high places without scaffolding



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping

Distributed by: