



900/1400 Series

Hot-Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

U.S. Design Patent No. 740,501 S

Electric / Belt Drive



Upright, vertical coil with 1/2-inch schedule 80 pipe is wrapped with a thick foil blanket insulation, delivering high efficiency and maintains constant temperature using Natural Gas or LP Gas

Industry-standard **flue outlet** for quick installation

Pressure relief valve protects the machine and user from thermal expansion

Improved **auto-tensioning** system maintains belt tension on the pump with a torsion bar for precise tension adjustment

Triple banded belt for more efficient power transmission


Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning



Hotsy-designed Triplex pumps carry a 7-year limited warranty

Same **footprint** as previous generation for easy upgradability

Programmable Smart Control Automation provides complete control over the machine's run time, auto start/shut down and time delay shut down functionality.



Locking lid prevents accidental removal of both panels around the belt and pulley

Concealed but accessible **Thermostat** reduces random user adjustments

Prewired to accept field installations of **remote controls**

Sleek side and front removable **panels** provide easy access to the entire washer for service & maintenance

50-ft. length of high-pressure hose for easy cleaning in a large working area



FEATURES

- 4.0 - 5.0 GPM @ 2000 to 3000 PSI
- NG Fired or LP Fired
- 208V or 230V, 1PH; 208V, 230V, 460V or 575V, 3PH
- ETL-Certified to UL-1776 safety standards

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Insulated Hotsy trigger gun and insulated wand with ergonomic, adjustable side handle

www.Hotsy.com

Nothing Cleans Like a Hotsy!

900 / 1400 SERIES Hot-Water ELECTRIC Models

■ NG-Fired or LP-Fired ■ 4.0 to 5.0 GPM @ 2000 to 3000 PSI ■ Hotsy Triplex Pump with 7-yr warranty ■ ETL-Certified for safety

Stationary pressure washers for heavy-duty cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
921P	4.0	2300	6.2	3450	208/1	28	LP	364,835	HHC506R.2	50'	700
921N	4.0	2300	6.2	3450	208/1	28	NG	364,835	HHC506R.2	50'	700
926P	4.0	2000	5	1800	575/3	7	LP	364,835	HHC506R.2	50'	660
926N	4.0	2000	5	1800	575/3	7	NG	364,835	HHC506R.2	50'	660
942P	4.0	2000	5	1725	208/3	18	LP	360,997	HM4030R.3	50'	590
942N	4.0	2000	5	1725	208/3	18	NG	364,835	HM4030R.3	50'	655
943P	4.0	2000	5	1725	230/1	25	LP	360,997	HM4030R.3	50'	685
943N	4.0	2000	5	1725	230/1	25	NG	364,835	HM4030R.3	50'	685
944P	4.0	2000	5	1725	230/3	16	LP	360,997	HM4030R.3	50'	580
944N	4.0	2000	5	1725	230/3	16	NG	364,835	HM4030R.3	50'	680
945P	4.0	2000	5	1725	460/3	8	LP	360,997	HM4030R.3	50'	585
945N	4.0	2000	5	1725	460/3	8	NG	364,835	HM4030R.3	50'	585
1451P	4.0	3000	8.2	3450	208/1	42	LP	364,835	HHC506R.2	50'	730
1451N	4.0	3000	8.2	3450	208/1	42	NG	364,835	HHC506R.2	50'	730
1452P	4.0	3000	7.5	1725	208/3	24	LP	360,997	HM4030R.3	50'	625
1452N	4.0	3000	7.5	1725	208/3	24	NG	364,835	HM4030R.3	50'	625
1453P	4.0	3000	7.5	1725	230/1	34	LP	360,997	HM4030R.3	50'	735
1453N	4.0	3000	7.5	1725	230/1	34	NG	364,835	HM4030R.3	50'	735
1454P	4.0	3000	7.5	1725	230/3	24	LP	360,997	HM4030R.3	50'	625
1454N	4.0	3000	7.5	1725	230/3	24	NG	364,835	HM4030R.3	50'	700
1455P	4.0	3000	7.5	1725	460/3	12	LP	360,997	HM4030R.3	50'	630
1455N	4.0	3000	7.5	1725	460/3	12	NG	364,835	HM4030R.3	50'	780
1456P	4.0	3000	8.2	3450	575/3	10	LP	364,835	HHC506R.2	50'	621
1456N	4.0	3000	8.2	3450	575/3	10	NG	364,835	HHC506R.2	50'	621
1473P	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	50'	735
1473N	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	50'	735
1474P	5.0	3000	10	1770	230/3	29	LP	378,617	HM4035R.3	50'	740
1474N	5.0	3000	10	1770	230/3	29	NG	390,025	HM4035R.3	50'	740
1475P	5.0	3000	10	1725	208/3	32	LP	378,617	HM4030R.3	50'	740
1475N	5.0	3000	10	1725	208/3	32	NG	378,617	HM4030R.3	50'	740

Dimensions: 47.5"l x 21"w x 51"h (including connectors and flue outlet)

OPTIONS FOR 900/1400 SERIES

- Remote Controls for start up, shut down
- 8" Gas-Fired Draft Diverter - for natural draft burner operation; prevents downward/upward air affecting burner efficiency
- Wheel Kit - includes LP bottle rack & clamp; platform cart enables mobility; 2 swivel casters, 2 rigid
- Inlet Water Solenoid - prohibits water flow to float tank during idle
- Soap Solenoid - use with remote station for on/off detergent control

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.

FIND OUT MORE ONLINE: HOTSY.COM



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 9.801-491.0 Effective 3/16



Specifications & product descriptions subject to change without notice.
 Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.
 A member of KÄRCHER North America ©2016 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at ± 10% and in some cases are tighter within ± 5% of listed specifications.